

Model No.:FTB-16L-1


1 Overview

YIPU Model No. FTB-16L-1 can connect the drop cable with feeder cable as the termination point in the Fttx network, which is cable to meet at least 16 users requirements. It can help splicing, splitting, storage and management with suitable space.

2 Technical Index

Model No.	FTB-16L-1	Color	Black, Grey White..
Capacity	16cores	Protection Level	IP55
Material	PC+ABS, ABS	Flame retardant performance	Non-flame retardant
Dimension(L*W*D,MM)	320*210*125	Splitter	Can be with 2x1:8 & 1x1:16 tube splitter

The dimension diagram:(mm)



3 Features

- 3.1 The body is made of high quality engineering plastic with good strength;
- 3.2 With safe special-shaped lock, the box can be opened easily and has good water-proof performance, suitable for indoor and outdoor natural environments (Pic#4 for details);

HANGZHOU HI LINK ELECTRONICS CO.,LTD

The Datasheet of Fiber Optical Terminal Box

3.3 With water-proof adapter, the box can be operated more conveniently (Pic#5 for details);

3.4 With double-page design, the box can be installed and maintained easily, the fusion and termination are completely separated (Pic#6 for details);

3.5 The drop leaf can be installed 1 pcs of 1*8 tube splitter (Pic#7 for details);


Pictures for reference:

For 3.2




Pic#4

For 3.3




Pic#5

For 3.4



Pic#6

For 3.5



Pic#7

4 Package Information

4.1 Plastic bag size: 500*410mm

4.2 Inner box with single corrugated size:330*220*135mm

4.3 Carton with double corrugated size:695*350*460mm(10PCS/Box)